



Material:
 Insulator: PBT+30% Glass Fiber (UL94V-0).
 Contact: Copper Alloy.
 Contact Plated: Gold or Tin over Nickel Plated.
 Specification:
 Current Rating: 1 Amp.
 Withstanding Voltage: AC 500V for 1 Minute.
 Insulation Resistance: 1000MΩ Min. at DC 500V.
 Contact Resistance: 15mΩ Max.
 Operating Temperature: -40°C ~ +105°C.

Pos.	Dim. A	Dim. B	Dim. C	Dim. D
10	31.90	21.84	10.16	27.94
14	36.98	26.92	15.24	33.02
16	39.52	29.46	17.78	35.56
20	44.60	34.54	22.86	40.64
24	49.68	39.62	27.94	45.72
26	52.22	42.16	30.48	48.26
30	57.30	47.24	35.56	53.34
34	62.38	52.32	40.64	58.42
40	70.00	59.94	48.26	66.04
50	82.70	72.64	60.96	78.74
60	95.40	85.34	73.66	91.44
64	100.48	90.42	78.74	96.52

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

L-RD34-xx-LF
 SERIES LEADFREE
 10~64WAY
 DIP 3.4mm
 DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54mm Ejector Box Header Right Angle Type