



**REMARK:**



(1)(3) CONNECTOR TYPE:

A--FC; B--SC; C--ST; L--LC;  
 0--NONE [PIGTAIL FOR (3)]  
 OTHER TYPE--PLEASE SPECIFY.

(2)(4) CONNECTOR POLISHING GRADE:

P--PC; S--SPC; U--UPC; A--APC;  
 0--NONE [PIGTAIL FOR (4)]

(5) CABLE MODE TYPE:

S--SINGLEMODE; M--MULTIMODE;

(6) FIBER TYPE:

10--9/125um S/M; 20--50/125um M/M;  
 21--62.5/125um M/M;

(7) CABLE TYPE:

S--SIMPLEX; D--DUPLEX(ZIPCORD);  
 R--ROUND CORE DUPLEX;

(8)CABLE OD TYPE:

30--3.0mm; 09--0.9mm; 20--2.0mm;  
 24--2.4mm; 18--1.8mm;

(9) CABLE LENGTH:

0005--0.5M; 0010--1M; 0020--2M; 0030--3M;  
 0100--10M; 0200--20M; \*THE REST CAN BE SPECIFIED

(10) CABLE MARKER:

A--3A; B--BAYCOM; C--SIECOR; X--OTHER,NONE;

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT/mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

SIZE A4

PPOJECTION

照片框

**ORDER INFORMATION**

**LCX1-1S00-M6M-LF**  
 SERIES | LEADFREE  
 | 6000mm  
 | MALE TO MALE  
 ST

DESCRIPTION:

[www.morethanall.com](http://www.morethanall.com)