

P.C.B. LAYOUT

SPECIFICATIONS:

1. INSULATION RESISTANCE: 100M OHM AT 500V D.C.
2. DIELECTRIC STRENGTH: 1,000V AC / 1 MINUTE.
3. CONTACT RESISTANCE: 20m OHM MAX.
4. RATING: 100V A.C. 2A

LS-JR-02-LF  
LEADFREE

RoHS Compliant

4	CONTACT TERMINAL	1	BSR-H 0.7 <sup>t</sup>	Sn	
3	SPRING TERMINAL	1	PBR 0.25 <sup>t</sup>	Sn	
2	CONTACT TERMINAL	1	BSR-H 0.3 <sup>t</sup>	Sn	
1	BODY	1	P.B.T.		UL94V-0
P/N	PART NUMBER	Q'TY	MATERIAL	PLATING	REMARKS
件號	名稱	數量	材 質	處 理	備 註

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO. **LS-JR-02**

DWG NO. **LS-JR-02**

CHECKED BY CY

TOLERANCES ARE

.X±0.2

.XX±

.XXX±

AWG

DESCRIPTION:

焯倫股份有限公司


FILE NO.

DRAWING BY

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE