



注：

- 1.\*为重点检验尺寸
- 2.点胶不可超过CONN表面
- 3.绝缘阻抗:DC/200V 10MΩ MIN.
- 4.耐电压:AC/200V 2mA FOR 0.01 SECONDS.
- 5.导通阻抗:3Ω MAX.

P1		P2	P1		P2
1	40# 蓝	1	21	40# 蓝	21
2	40# 蓝	2	22	40# 蓝	22
3	40# 蓝	3	23	40# 蓝	23
4	40# 蓝	4	24	40# 蓝	24
5	40# 蓝	5	25	40# 蓝	25
6	40# 蓝	6	26	40# 蓝	26
7	40# 蓝	7	27	40# 蓝	27
8	40# 蓝	8	28	40# 蓝	28
9	40# 蓝	9	29	40# 蓝	29
10	40# 蓝	10	30	40# 蓝	30
11	40# 蓝	11	31	40# 蓝	31
12	40# 蓝	12	32	40# 蓝	32
13	40# 蓝	13	33	40# 蓝	33
14	40# 蓝	14	34	40# 蓝	34
15	40# 蓝	15	35	40# 蓝	35
16	40# 蓝	16	36	40# 蓝	36
17	40# 蓝	17	37	40# 蓝	37
18	40# 蓝	18	38	40# 蓝	38
19	40# 蓝	19	39	40# 蓝	39
20	40# 蓝	20	40	40# 蓝	40
			铁壳	编织	铁壳

序号	材料规格	用量	材料廠商	備註
1	WIRE: UL1354 40# OD:0.32mm PET 50欧姆蓝色同轴线	40PCS		
2	CONN: HONDA LVD 40PIN, "一字型" 2.0H(HLX09006)	2SET	威利科 OR EQ	
3	黑色拉带: PET+3M467 规格: 7*105.5*0.075	2PCS	铭展	
4	纳米胶带: W10MM, T=0.08MM, 黑色	0.15M	铭展	
5	单边热压铜片: W0.5MM, T=0.1MM	4PCS	涵海	
6	锡膏:	AR		
7	UV胶:	AR		

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

LVCX2-404040-M13C-LF

SERIES 40# LEADFREE  
40 TO 40 WAY MALE TO MALE  
130mm

DESCRIPTION: WIRE HARNESS

煜倫股份有限公司

www.morethanall.com