


Recommended
P.C. Board
Hole Layout



Specifications

- Current Rating : 2 Amps
- Insulator Resistance : 1000 Megohms min.
- Contact Resistance : 20 m ohms max.
- Dielectric Withstanding : AC 500V
- Operating Temperature : -40°C ~ +105°C
- Contact Material : Brass
- Insulator Material : Polyester, UL 94V-0
- Standard : Nylon-6T
- Contact Plated : Full Gold, Full Tin, Selective Plated

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

.XXX±

ANG±

DATE

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

M-D10xxyy-2Xxx-LF
 SERIES | | | | LEADFREE
 | | | | 2X02:04WAY
 | | | | 2X50:100WAY
 DIP180° | | | | 25:DIP 2.5mm
 | | | | 28:DIP 2.8mm
 BASE 1.0mm | | | | 25:CONTACT 2.5mm
 | | | | 40:CONTACT 4.0mm

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com