



Recommended P.C.B Layout

MATERIAL

Insulator : 30% Glass fiber PBT

Contact Pin : Brass

SPECIFICATION


Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C



POLES	DIM E	POLES	DIM E
2	2.00	21	40.00
3	4.00	22	42.00
4	6.00	23	44.00
5	8.00	24	46.00
6	10.00	25	48.00
7	12.00	26	50.00
8	14.00	27	52.00
9	16.00	28	54.00
10	18.00	29	56.00
11	20.00	30	58.00
12	22.00	31	60.00
13	24.00	32	62.00
14	26.00	33	64.00
15	28.00	34	66.00
16	30.00	35	68.00
17	32.00	36	70.00
18	34.00	37	72.00
19	36.00	38	74.00
20	38.00	39	76.00
		40	78.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE


SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

PPOJECTION

照片框

ORDER INFORMATION



DESCRIPTION: PIN HEADER 2.00*2.00mm RIGHT ANGLE TYPE, SINGLE ROW