



TABLE A

Item	Description	Material	UL File No.
1	Insulation	1403G6	E130155
2	Pin	AS H3250 C3604 B0	
3	Shell	C3604	
4	O-Ring	NBR	
5	YGLUE	5339A/B	E105126

- MATERIAL**
 INSULATION: THERMOPLASTIC UL94V-0
 COLOR: BLACK.
 CONTACT: BRASS
 SHELL: BRASS
- PLATING**
 CONTACT: CONTACT PLATED 30u" GOLD,
 Shell: NICKEL 100u"
- SPECIFICATION**
 CURRENT: 2 A.
 OPERATING TEMPERATURE: -20° C TO 105° C.
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN.
 DIELECTRIC STRENGTH: 500V AC MIN.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

M12-SDPANO-05-LF
 SERIES | | | LEADFREE
 | | | 05 WAY
 | | | O-RING
 FEMALE | | NUT
 | | | PANEL FRONT
 DIP 180°

DESCRIPTION: