



Note:

1. Waterproof Rate: IP67 (With Mating)
(No Ingress Of Dust/ Protected Against Harmful Effects Caused In 1 Meter Water Within 30 Minutes With Mating)
2. Temperature Range: -25°C to +85°C
3. Current Rating: 0.5A
4. Voltage Rating: AC 50V /DC 60V
5. Transfer Category: Cat.6A
6. Insulation Diameter: $\phi 0.9 \sim \phi 1.13 \text{mm}$
7. Cable Diameter: $\phi 5.5 \sim \phi 8.0 \text{mm}$
8. Material:
Housing: Nylon, Black
Pin: Copper Alloy, Gold Plated
Screw Nut: Zinc Alloy, Nickel Plated
Body: Brass, Nickel Plated
Sealing Nut: Brass, Nickel Plated
O-Ring: Rubber
9. One Set Unassembled In One PE Bag

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X \pm 0.25
.XX \pm 0.10
.XXX \pm 0.05
ANG \pm 1°

PPOJECTION

照片框

ORDER INFORMATION

M12-SIFM26-08X-LF
SERIES | LEADFREE
| 08 X CODE
| 26AWG
| FULL METAL
IDC
FEMALE

DESCRIPTION: SENSOR, M12, ASSY, F CONN. F PIN, SCREW