



PIN OUT		
M12-4PIN FEMALE		
1	BROWN	NC
2	WHITE	NC
3	BLUE	NC
4	BLACK	NC
COUPLING NUT	DRAIN WIRE	NC

### \*\*\*CONSTRUCTION:

#### 1.CABLE:

- \* UL2661 (4C/22#)+(ALUMINUM-MYLAR FOIL+22# DRAIN WIRE)  
OD:7.3mm YELLOW PVC JACKET.

### \*\*\*CONNECTORS:

#### 2.M12-5PIN:

- \* M12-4PIN FEMALE SOLDER TYPE.
- \* PIN: BRASS WITH TIN PLATED.
- \* INSULATOR: BLACK NYLON 66 UL 94V-0 RATED.
- \* COUPLING NUT: M12x1 BRASS WITH NICKEL PLATED.
- \* GASKET: SILICONE RUBBER BLACK COLOR.
- \* FERRULE: BRASS WITH NICKEL PLATED.
- \* MOLDED: PUR YELLOW COLOR.

#### 3.TEST:

- \* CT: 2 Ohm. IS: 5M Ohm.
- \* RATE CURRENT: 4A RATE VOLTAGE: 250V

#### 4.PACKING:

- \* PACK EACH CABLE IN A POLY BAG.

#### 5.MATERIAL:

- \* MATERIAL WITH RoHS GRADE.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

### ORDER INFORMATION

M12X1-040022YL-Fxxx-LF

SERIES

04 WAY

22 AWG

YL:YELLOW

FEMALE

25F:25 FEET

15F:15 FEET

6F: 6 FEET

LEADFREE

DESCRIPTION: