



FRONT VIEW

M12-5PIN MALE
MOLDED BLACK

***CONSTRUCTION:

1.CABLE: * UL2464(5C/24#)+T OD:5.0mm BLACK PVC JACKET.

***CONNECTORS:

2.M12-5PIN: * M12-5PIN MALE SOLDER TYPE.
* PIN: BRASS WITH GOLD PLATED.
* INSULATOR: BLACK NYLON 66 UL 94V-0 RATED.
* SHELL: BRASS WITH NICKEL PLATED.
* FERRULE: BRASS WITH NICKEL PLATED.
* MOLDED: PVC 45P BLACK COLOR.

3.TEST: * CT: 2 Ohm. IS: 5M Ohm.
* RATE CURRENT: 4A RATE VOLTAGE: MAX.60V

4.PACKING: * PACK EACH CABLE IN A POLY BAG.

5.MATERIAL: * MATERIAL WITH RoHS GRADE.

PIN OUT

M12-5M

1	BROWN	NC
2	WHITE	NC
3	BLUE	NC
4	BLACK	NC
5	YELLOW/GREEN	NC
SHELL	DRAIN	NC

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

M12X1-050024BK-M1M-LF

SERIES

05 WAY

24 AWG

BLACK

MALE

LEADFREE

1000mm

DESCRIPTION: