


PIN OUT

M12-8PIN FEMALE

1	WHITE	NC
2	BROWN	NC
3	GREEN	NC
4	YELLOW	NC
5	GREY	NC
6	PINK	NC
7	BLUE	NC
8	RED	NC
NC	DRAIN WIRE	NC



MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

M12X1-08R4524BK-Fxx-LF

SERIES

8 PIN 90°

45 DEG

24AWG

BLACK

LEADFREE

2M:2000mm

5M:5000mm

10M:10000mm

FEMALE

DESCRIPTION: M12-8PIN FEMALE TO OPEN (BLACK PVC JACKET)

***CONSTRUCTION:

1.CABLE: * UL2464 (8C/24#)+EA OD:5.2mm BLACK PVC JACKET(-40°C~+80°C).

***CONNECTORS:

2.M12-8PIN: * M12-8PIN FEMALE SOLDER TYPE.
* PIN: BRASS WITH GOLD PLATED.
* INSULATOR: BLACK NYLON 66 UL 94V-0 RATED.
* COUPLING NUT: M12x1 BRASS WITH NICKEL PLATED.
* O-RING: SILICONE RUBBER RED COLOR.
* FERRULE: BRASS WITH NICKEL PLATED.
* MOLDED: BLACK PVC 45P.

3.TEST: * CT: 2 Ohm. IS: 20M Ohm. DC300V/0.1S

4.ELECTRICAL: * CURRENT RATING: 2A VOLTAGE RATING: 30V

5.WATERPROOF: * IP 68, NEMA 8P

6.PACKING: * PACK EACH CABLE IN A POLY BAG.

7.MATERIAL: * MATERIAL WITH RoHS GRADE.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

M12X1-08R4524BK-Fxx-LF

SERIES

8 PIN 90°

45 DEG

24AWG

BLACK

LEADFREE

2M:2000mm

5M:5000mm

10M:10000mm

FEMALE

DESCRIPTION: M12-8PIN FEMALE TO OPEN (BLACK PVC JACKET)