



Rated current/voltage: 15A 250V
 Operation limit voltage: 400V
 Withstanding voltage: 1500
 Insulation resistanceDV500V: 2000MΩ
 Contact resistanceDC1A: 10mΩ

技术要求 (Techique Request):

- 1.外表光滑, 周边无毛刺
(Sleek in appearance, no burrs in periphery);
- 2.螺纹旋入顺畅
(Thread can screw in smoothly);
- 3.与母座配插顺畅
(It should match the male connector smoothly).

8		铆钉 (RIVER)	1		
7		塑盖 (PLASTIC COVER)	1		
6		锌壳 (DIE-CAST SHELL)	1	ZZnA14-1	镀镍M25X1
5		螺丝 (BOLT)	3	A3	
4		橡胶垫片 (PLASTIC WASHER)	1	RUBBER	
3		弹簧 (SPRING)	1	65Mn	镀镍 (NICKEL PLATED)
2		胶木 (BAKELITE)	1	BAKELITE	
1		插针 (PIN)	4	59-1	镀金 (GOLD PLATED)
序号	图号	名称	数量	材料	备注

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm
 DATE

SCALE 1 : 1

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

M25-PSPCC-04-LF
 SERIES | | | | LEADFREE
 | | | | 04 WAY
 | | | | CHAIN
 | | | | COVER
 | | | | PROTECTIVE
 MALE | | | | SOLDER

DESCRIPTION: