


PACKING: 单PCS理线.  
100PCS/PE袋



PIN OUT

P1	P2
1	1 RED (红)
2	2 WHITE (白)
3	3 GREEN (绿)
4	5 BLACK (黑)
SHELL	BRAID
	SHELL (编织)

PART LIST:本产品均符合"ROHS"环保标准,用的材料均为相当品。

5	六角螺母 M3螺牙*12MM. 长12.5MM.	2	PCS
4	OUTER MOLDED:45P PVC BLACK.		Kg/1K
3	MINI 5P/M 焊线式 黑胶芯 铁壳镀镍 PIN针G/F.	1	SET
2	USB B/F 焊线式 白胶芯 铁壳镀镍 PIN针G/F.	1	SET
1	USB UL2725 28AWG*1P+28AWG*2C+AB OD:3.5mm 黑色PVC.	1	PCS
ITEM	STANDARD SPECIFICATION	Q' TY	UNIT

- ELECTRONIC TEST:
- 100% TEST,(Open,Short,Miss Wire).
  - Conduct Resistance: 1Ω/max.
  - Insulation Resistance: 20MΩ/min.
  - Hi-Pot: 300v dc/10ms.

RoHS Compliant

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司  
www.morethanall.com

DRAWING BY		TOLERANCES ARE
CY	X. ±	
CHECKED BY	.X ±	
GENIUS	.XX ±	
UNIT / mm	.XXX ±	
SCALE 1 : 1	ANG ±	
DATE		
SIZE A4	PJECTION	



ORDER INFORMATION

MBUB-5B4B28PB-E12N5-LF			
SERIES			LEADFREE
			318mm
			MALE TO FEMALE
			PANEL BACK
			28 AWG
			5 PIN B TYPE TO 4 PIN B TYPE

DESCRIPTION: