



PCB MOUNTING HOLE
(印刷电路板架設孔)

TYPICAL SPECIFICATIONS

1.0. ELECTRICAL

- 1.1. FREQUENCY RANGE: DC-6 GHz
- 1.2. NOMINAL IMPEDANCE: 50 OHM
- 1.3. WORKING VOLTAGE: 335 VOLTS MAX.
- 1.4. PROOF VOLTAGE: 1000 VOLTS

2.0. MATERIALS

- 2.1. BODIES: BRASS PER JIS-C3604
- 2.2. CENTER CONTACT: PHOSPHOR BRONZE PER JIS-C5441
- 2.3. INSULATION: PTFE PER ASTM D1457 AND ASTM D1710

3.0. ENVIRONMENTAL

- 3.1. OPERATING TEMPERATURE RANGE: -55° C TO +155° C

3	CONTACT PIN	PB CU	GOLD	1	
2	INSULATOR	PTFE	WHITE	1	
1	BODY	BRASS	GOLD	1	
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ±

PJECTION

照片框

ORDER INFORMATION

MCX-JD-50-LF
SERIES | LEADFREE
50 OHM
DIP 180°
JACK

DESCRIPTION: