



PCB LAYOUT(REF.)

TYPICAL SPECIFICATIONS:

1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-6 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHM
- 1.3 WORKING VOLTAGE: 335 VOLTS MAX.
- 1.4 PROOF VOLTAGE: 1000 VOLTS

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: PHOSPHOR BRONZE PER JIS C5441
- 2.3 INSULATION: PTFE PER ASTM D1457 AND ASTM D1710

3.0 ENVIRONMENTAL

- 3.1 OPERATING TEMPERATURE RANGE: -55° C TO +155° C

| NO | DESCRIPTION | MATERIAL | Q'TY | FINISH |
|----|-------------|-----------------|------|--------|
| 3 | PIN | PHOSPHOR BRONZE | 1 | GOLD |
| 2 | INSULATION | TEFLON | 1 | NONE |
| 1 | BODY | BRASS | 1 | GOLD |

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.20
 .XX ± 0.10
 .XXX ± 0.05
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MCX-JE17-50-LF
 SERIES | LEADFREE
 50 OHM
 EDGE CLIP 1.73mm
 JACK

DESCRIPTION: