



NOTES

- 1. FREQ.RANGE : DC~4GHz
- 2. IMPEDANCE : 50Ω NOMINAL
- 3. VSWR : 1.15: 1 MAX
- 4. CABLE : RG405/U(.085)
- 5. ATTACHMENT : DIRECT SOLDER

| NO | PART NAME | SPECIFICATION | Q'TY |
|----|-------------|-----------------------------|------|
| 1 | BODY | BeCu(C1730 B) , TCP PLATING | 1 |
| 2 | PIN | BeCu(C1730 B) , Ag PLATING | 1 |
| 3 | INSULATOR | TEFLON(PTFE) | 1 |
| 4 | SOLDER BODY | Bs(C3604BD) , TCP PLATING | 1 |
| 5 | CAP | Bs(C3604BD) , TCP PLATING | 1 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION

| | |
|-----------|-------|
| 0.5-5 | =±0.2 |
| 5-30 | =±0.4 |
| 30-120 | =±0.6 |
| 120-315 | =±1 |
| 315-1000 | =±1.6 |
| 1000-2000 | =±2.4 |

照片框

ORDER INFORMATION

MCX-PCRPE1-405-LF
SERIES | | | | LEADFREE
| | | | RG405
| | | | PANEL EAR
| | | | 90°
| | | | CRIMP
| | | | PLUG

DESCRIPTION: MCX plug R/A dip 90 for RG405U