



SPECIFICATIONS:

1.CURRENT CARRYING CAPACITY:

AC : 100V 1A MAX. DC : 12V 2A MAX.

2.CONTACT RESISTANCE: 30m OHM MAX.

3.INSULATION RESISTANCE:50M OHM MIN. AT DC 250V

4.VOLTAGE WITHSTANCE : AC 250V FOR ONE MINUTE

5.INSERTION FORCE : 1.0~4.5 KGF

WITHDRAWAL FORCE : 0.8~3.0KGF

3	CONTACT TERMINAL	*	BSR-H 0.2T	TIN PLATED	N/A
2	EARTH TERMINAL	1	BSR-H 0.4T	TIN PLATED	N/A
1	BODY	1	P.B.T	BLACK	UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING&COLOR	REMARKS

RANGEMENT OF CONTACTS						
OF CONTACTS	3	4	5	6	7	8

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

MDC-SPBE-xx-LF
SERIES | | | | LEADFREE
| | | | 03-08WAY
| | | | EAR
| | | | BACK
| | | | PANEL
| | | | SOCKET

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: