


标签规格:



TEST REQUIREMENTS/测试要求:  
 OPEN/SHORT TEST/导通测试: 100%;  
 CONDUCTOR RESISTANCE/导通阻抗: 2Ω (MAX);  
 INSULATION RESISTANCE/绝缘阻抗: 10MΩ (MIN);  
 HI-POT TEST/高压测试: 150V/AC, 300V/DC

BOM表

|            |                          |                                                                |             |            |
|------------|--------------------------|----------------------------------------------------------------|-------------|------------|
| 6          | LG-BOX-H445*205*95-RS    | H737加强芯外销纸箱: 445*205*95MM                                      | pcs/箱       |            |
| 5          | LG-PE-850*700*0.03-02-RS | 防水袋: 850*700*0.03mm RoHS                                       | pcs/袋       |            |
| 4          |                          | 黄底黑子标签 W=10* L=30mm                                            | 1           | PCS        |
| 3          |                          | 黑色热缩套管Φ1.0*8mm                                                 | 4           | PCS        |
| 2          | LA-DD4PM-BK-08-RS        | MINI DIN 4pin 八件套组装式                                           | 2           | PCS        |
| 1          | LS-159-049               | (RG174/U 26AWG*1C+B)*2F 芯线颜色: 红 白<br>OD:2.8*5.6<br>L=5100±10mm | 1           | PCS        |
| ITEM<br>序号 | PART No.<br>料号           | SPECIFICATION<br>品名规格                                          | Q' TY<br>数量 | UNIT<br>单位 |

接线表

| 4P公头 |    | 4P公头 |
|------|----|------|
| Pin1 | 白色 | Pin1 |
| Pin2 | 编织 | Pin2 |
| Pin3 | 编织 | Pin3 |
| Pin4 | 红色 | Pin4 |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±  
 X, ±  
 .XX ±  
 .XXX ±  
 ANG ±

照片框

ORDER INFORMATION

MDLX2-040426-M5M-LF

SERIES

LEADFREE

5000mm

MALE TO MALE

26 AWG

04 TO 04 WAY

DESCRIPTION: