



NOTES:

- 1.100% OPEN OR SHORT TEST
- 2.VOLTAGE:300V DC/10s
- 3.INSULATION RESISTANCE:5M ohm MIN
- 4.CONTACT RESISTANCE:5 ohm MAX
5. The product is ROHS compliant.

4	OUTER MOLD	黑色 45P PVC	2
3	INNER MOLD	低密度PE料	2
2	CONNECTOR	MINI DP 公头，端子镀金，白色胶芯，外壳镀镍	2
1	CABLE	[(7/0.08)*1P+AL+MYLAR]*5P+(7/0.08)*4C+(7/0.10)*1C+ADB+(16*7/0.12AL) PVC外被 黑色 OD:5.5mm	1
NO	NAME	Description	Q' TY

RoHS Compliant



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

TOLERANCES ARE

- X. ±
- .X ± 0.25
- .XX ± 0.15
- .XXX ± 0.05
- ANG ±



ORDER INFORMATION

MDSPX2-20203032-M2M1-LF

SERIES

LEADFREE
2100mm
MALE TO MALE
30/32 AWG
20 TO 20 WAY

DESCRIPTION: