



A: 15.00 mm

B: 2.50 mm

C: 2.50 mm

D: 10.00 mm

MATERIAL

HOUSING :PBT, UL-94V0

COLOR :BLACK

CONTACT :BRASS

PLATED :GOLD-FLASH

SPECIFICATION

CURRENT : 1.5A

OPERATING TEMPERAURE : -55° C TO +105° C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE: 1000 MEGAOHMS MIN

WITHSTAND VOLTAGE : 500 V AC/Minute

CONTACTS			
	1 × 11	1 × 21	1 × 31
1 × 02	1 × 12	1 × 22	1 × 32
1 × 03	1 × 13	1 × 23	1 × 33
1 × 04	1 × 14	1 × 24	1 × 34
1 × 05	1 × 15	1 × 25	1 × 35
1 × 06	1 × 16	1 × 26	1 × 36
1 × 07	1 × 17	1 × 27	1 × 37
1 × 08	1 × 18	1 × 28	1 × 38
1 × 09	1 × 19	1 × 29	1 × 39
1 × 10	1 × 20	1 × 30	1 × 40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ± 5°

PPOJECTION

照片框

ORDER INFORMATION

ME-D1502525-1Xxx-LF

SERIES

DIP 180°

LEADFREE
1X02:02WAY
1X40:40WAY
DIP:2.5mm
CONTACT 2.5mm
TOTAL 15.0mm

DESCRIPTION: PIN HEADER 2.00 五塑 180° H:2.00 1*XXPIN

煜倫股份有限公司

www.morethanall.com