



MATERIAL&FINISH

Insulator: PBT Glass Fiber(UL94V-0)

Contact : Brass

Contact : Gold-Plated Over Nickel.

SPECIFICATIONS

Current Rating : 1A AC,DC

Voltage Rating : 250V AC,DC

Temperature Range: -40°C To +105°C

Contact Resistance: 20mΩ Min

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 500V AC/Min

No.	A	B	C	No.	A	B	C	No.	A	B	C
06	10.20	4.00	5.00	20	24.20	18.00	19.00	36	40.20	34.00	35.00
08	12.20	6.00	7.00	22	26.20	20.00	21.00	40	44.20	38.00	39.00
10	14.20	8.00	9.00	24	28.20	22.00	23.00	44	48.20	42.00	43.00
12	16.20	10.00	11.00	26	30.20	24.00	25.00	50	54.20	48.00	49.00
14	18.20	12.00	13.00	28	32.20	26.00	27.00	60	64.20	58.00	59.00
16	20.20	14.00	15.00	30	34.20	28.00	29.00	64	68.20	62.00	63.00
18	22.20	16.00	17.00	34	38.20	32.00	33.00				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

MF-C2A-xxx-LF
SERIES | LEADFREE
006~064WAY
A TYPE
TWO TYPE

DESCRIPTION: