



Material:

Housing: Thermoplastic Polyester Glass Filled UL94V-0.

Contacts: Copper Alloy.

Cable: 1.00mm(0.039") pitch flat cable.

Electrical Characteristics:

Current Rating: 1 AMP.

Dielectric Withstanding Voltage: AC 500V.

Insulator Resistance: 1000MΩ min. at DC 500V.

Contact Resistance: 30mΩ max. at DC 100mA.

Operating Temperature: -40°C~+105°C.

*RoHS Compliant

Position	Dimension	
	A	B
10	15.25	8.00
12	17.25	10.00
14	19.25	12.00
16	21.25	14.00
18	23.25	16.00
20	25.25	18.00
22	27.25	20.00
24	29.25	22.00
26	31.25	24.00
30	35.25	28.00
34	39.25	32.00
40	45.25	38.00
44	49.25	42.00
50	55.25	48.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

照片框

ORDER INFORMATION

MF-C3X-xxx-LF
SERIES | LEADFREE
010~050WAY
NON NOSE
THREE TYPE

DESCRIPTION: