

Features:

- 600V volts rating (R.M.S.)

Specifications:


- Voltage rating: 600V AC, DC
- Current rating up to 9A (with #18 AWG)
- Dielectric withstanding Voltage: 1500V AC/minute
- Contact resistance: Initial value/10m Ω Max.
After environmental testing/20m Ω Max.
- Crimp resistance: 5m Ω Max,
- Terminal retention force: 3.0Kg Mn.
- Ambient temperature range: -40°C ~ 105°C
(including temperature rise)

Ordering Information

Part No.	Finished
MFB-MT-22	Tin-plated
MFB-MT-18	
MFB-MT-16	

Dimensional Information (mm)

Part No.	Dimension				Wire Size (AWG)	Material
	a	b	c	d		
MFB-MT-22	2.3	2.8	1.65	1.8	#22 ~ #28	Brass
MFB-MT-18	4.5	3.6	2.3	1.9	#18 ~ #24	
MFB-MT-16			2.8	2.4	#16	



△ Test point

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.40
.XX ± 0.25
.XXX ± 0.08
ANG ±

照片框

ORDER INFORMATION

MFB-MT-xx-LF
SERIES T 22:22~28AWG LEADFREE
18:18~24AWG
16:16 AWG
T:TIN
MALE

DESCRIPTION: