



Dimensional Information (mm)

Circuits	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E	Dim. F	Dim. G
2		5.4	10.1	25.0	36.0	8.7	13.4
4	4.2	9.6	14.3	29.2	40.2	12.9	17.6
6	8.4	13.8	18.5	33.4	44.4	17.1	21.8
8	12.6	18.0	22.7	37.6	48.6	21.3	26.0
10	16.8	22.2	26.9	41.8	52.8	25.5	30.2
12	21.0	26.4	31.1	46.0	57.0	29.7	34.4
14	25.2	30.6	35.3	50.2	61.2	33.9	38.6
16	29.4	34.8	39.5	54.4	65.4	38.1	42.8
18	33.6	39.0	43.7	58.6	69.6	42.3	47.0
20	37.8	43.2	47.9	62.8	73.8	46.5	51.2
22	42.0	47.4	52.1	67.0	78.0	50.7	55.4
24	46.2	51.6	56.3	71.2	82.2	54.9	59.6

Recommended Panel Cut-out for 1.27±0.3mm thickness panel

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

MFB-SH-2Xxx-LF
SERIES | LEADFREE
2X01:02WAY
2X12:24WAY
HOUSING
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION:

Features:

- 2 ~ 24 circuits available

Specification:

- Voltage rating: 600V AC, DC (R.M.S.)
- Current rating and wire size:

Maximum current rating (Amperes)					
Ampere Wire	Ckt Size	2	4, 6	8, 10	12~24
	AWG #16		9	8	7
AWG #18		7	6	5	4
AWG #20		6	5	4	4
AWG #22		5	4	4	4
AWG #24		4	3	3	3
AWG #26		2	1	1	1
AWG #28		1	1	1	1

- Insulation resistance: DC 500V 1000M Ω Min.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C
(including temperatute rise)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

PPOJECTION 

照片框

ORDER INFORMATION

MFB-SH-2Xxx-LF
SERIES | LEADFREE
2X01:02WAY
2X12:24WAY
HOUSING
FEMALE

DESCRIPTION: