



Note:

- (1) The orientation should be the same as shown. (加工製程需遵照圖面標示方向,IPEX朝上,D平面朝前)
 (2) C02AD31113005外部防水圈在妥善與機構鎖配後可達IP65

07	Nut	1
06	Washer	1
05	O-ring	1
04	SMA bulk Jack HEX11.0 with O-ring	1
03	Heatshrink (Black)	1
02	1.13-MIT coaxial cable (Gray)	1
01	I-PEX MHF Plug	1
NO	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MHF SMA-1R1S113IP65-E15C-LF

SERIES

RT/ST

IP65

1.13mm DIA CABLE

LEADFREE

150mm

MALE TO FEMALE

DESCRIPTION: IPEX to 1.13(GR) to SMA(F)st.bh.O-ring,L=150mm