



WIRE ARRANGEMENT		
P1	COLOR	P2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	5
CASE	BRAID SHIELD	CASE

4.	PLASTIC HOOD COLOR FOR BLACK
3.	USB CONN.: A TYPE,FEMALE,SOLDER TYPE, GOLD-FLASH. INSULATOR: PBT, WHITE. FRONT SHELL Ni-PLATED, BACK SHELL Ni-PLATED. WITH SPRING.
2.	MICRO USB B TYPE MALE BLACK INSULATED.
1.	CABLE: UL2725 28AWGx1P+28AWGx2C+AE. PVC JACKET BLACK. OD=φ3.0±0.15mm.
NO.	NOTES:

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MIBUB-5B4A28-Exxx-LF

SERIES

LEADFREE
CABLE LENGTH
MALE TO FEMALE
28AWG
5 PIN B TO 4 PIN A TYPE

DESCRIPTION: USB A (F) TO Micro 5P NL=150mm