



NOTE :
 * Material : Ployester UL 94V-0
 * Color : Black
 * Electrical rating : 250V 5A, AC/DC
 * 4-24 circuits available
 * Dual row

CIRCUITS	DIM.A	DIM.B	DIM.C	DIM.D
4	3.00	24.70	13.46	22.10
6	6.00	27.70	16.46	25.10
8	9.00	30.70	19.46	28.10
10	12.00	33.70	22.46	31.10
12	15.00	36.70	25.46	34.10
14	18.00	39.70	28.46	37.10
16	21.00	42.70	31.46	40.10
18	24.00	45.70	34.46	43.10
20	27.00	48.70	37.46	46.10
22	30.00	51.70	40.46	49.10
24	33.00	54.70	43.46	52.10

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.25
 .XXX ± 0.10
 ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

MIFB-SH-2Xxx-LF
 SERIES | LEADFREE
 2X02:04WAY
 2X12:24WAY
 HOUSING
 FEMALE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com