



Figure 10 shows the dimensions of the RS485 module. The module is 20.4 units wide and 88.3 units high. It is divided into two main sections, each 33.2 units high. The top section contains labels: RS485_A-BLUE, RS485_B-PNK, WDATA0-WHT, WDATA1-GRN, TAMPER-LT BLUE, BEEPER-YLW, RED_LED-BRWN, GRN_LED-ORNG, +12VDC-RED, and GND-BLK. The bottom section contains labels: RS485_A-BLUE, RS485_B-PNK, WDATA0-WHT, WDATA1-GRN, TAMPER-LT BLUE, BEEPER-YLW, RED_LED-BRWN, GRN_LED-ORNG, +12VDC-RED, and GND-BLK. A dimension of 22 is indicated for the top section.

3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	CABLE:	UL2464#26/10C(紅, 黑白, 綠)+T	1PCS	E238846
		外被:黑色半霧面 OD:6.0		
2	HOUSING:	MIF-SH-2X05	1PCS	E149293
3	TERMINAL:	MIF-FT-20	10PCS	
4	熱縮套管:	Ø10*30 F32 黑	1PCS	
5	標籤:	規格與內容如圖所示	1PCS	
6				
7				