



NOTES:

1.Material:

- 1.1:主体:LCP BLACK
- 1.2:护套:LCP BLACK
- 1.3:钢壳:SUS201, T=0.20±0.02mm.
- 1.4:卡钩:SUS201, T=0.40±0.05mm.
- 1.5:端子:H65,T=0.20±0.02mm

2.Finish:

- 2.1 端子:Test point:Ni 50u"/Au 1u" MIN. Δ
Soldering area:Ni 50u"/Tin(PB Free) 100u" MIN.
The other area:Ni 50u" MIN.
- 2.2 钢壳: Ni 30u" MIN.
- 2.3 盐雾测试: 24h

3.Specification:

3.1:Rating:

Rated voltage:AC 100V. Rated current:1A.

3.2:Electrical:

Contact resistance:
50m Ω MAX. at 20mV MAX, 50mA.
Insulation resistance:
100M Ω MIN. at 50V DC for 1Minute.
Dielectric withstanding voltang:
No discharge,flashover or breakdown
at 500V/AC 1Minute.

3.3:MECHANICAL:

INSERTION FORCE: 35N Max.
EXTRACTION FORCE: 8N Min.
DURABILITY: 5000 Cycles.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ± 5°

SIZE A4

PJECTION

照片框

ORDER INFORMATION

MISB-PM-5B-LF
SERIES | LEADFREE
| 5 PIN B TYPE
| MOLDING
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Micro 5P 单排7.20/前5后5