



Notes:

Specifications:

1. Current rating: 1 A Max.
2. Dielectric withstanding:voltage: 100V(AC) for 1 min.
3. Contact resistance: 50m  $\Omega$  Max.
4. Insulation resistance: 100M  $\Omega$  Min.
5. Total mating force: 3.57 Kgf Max.
6. Total unmating force: 1.0 Kgf Min.0.81~2.05 Kgf Min.after 10000 insertion/extraction cycles
7. Temperature range: -30°C~+80°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X,  $\pm$   
.X  $\pm$  0.25  
.XX  $\pm$  0.15  
.XXX  $\pm$  0.075  
ANG  $\pm$

P PROJECTION

照片框

ORDER INFORMATION

MISB-SVMX2156C-5B-LF

SERIES LEADFREE  
5 PIN B TYPE

FEMALE 180°SMT CAP  
NON POST FOOT DISTANCE 2.15mm & 5.60mm  
METAL FOOT

DESCRIPTION: MICRO USB 5 PIN SMT, TOP ENTRY WITH COVER