

## SPECIFICATION

**Rating:** 10.1A 125 / 250V AC.

**Contact resistance:**  $\leq 100\text{m}\Omega$  (initial)

**Insulation resistance:**  $\geq 100\text{M}\Omega$  at 500V DC.

**Withstand voltage:** 1,000V AC for 1 minute.

**Operating temperature:**  $-25^{\circ}\text{C} \sim +75^{\circ}\text{C}$ .

**Ambient humidity:**  $<70\%\text{RH}$ .

**Operating force:**  $150\pm 40\text{g}$ .

**Mechanical life:** 1,000,000 Cycles.

**Electrical life:** 6,000 Cycles.

**Note1:** Unwashable, don't be immersed by epoxy and organic solvent.


**Note2:** Please do not scale the drawing comparing to real product and kindly measure the size of real product.

## STORAGE METHOD

After opening the bag of the switches, please include a desiccant into the bag, then seal it to avoid product oxidation.

打開包裝袋後，請在袋中加入乾燥劑並「密封」，避免產品氧化。

## SCHEMATIC



## RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X,  $\pm$   
.X  $\pm$  0.30  
.XX  $\pm$  0.20  
.XXX  $\pm$   
ANG  $\pm$

照片框

## ORDER INFORMATION

MISW-D77-150-LF

SERIES

LEADFREE

150g

CONTACT PITCH 7.5+7.5mm

DIP 180°

DESCRIPTION: Micro Switch