






NOTE:

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.

1. MATERIAL:
HOUSING: PBT OR PA46, WITH GLASS FIBER,
UL 94V-0, STANDARD COLOR-BLACK.
CONTACTS: PHOSPHOR BRONZE.
2. FINISH:
CONTACTS: GOLD PLATED ON ENTIRE CONTACT,
 $1.27\mu\text{m}$ [$50\mu''$] MIN. NICKEL UNDERPLATED
ALL OVER.
3. "C" SHOWS QIP INSPECTION POINT.



DETAIL B
(SCALE 2:1)



RECOMMENDED PCB LAYOUT
RECOMMENDED PCB THICKNESS: 1.6mm
TOLERANCE: ± 0.05 (TOP VIEW)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, $\pm$
.X $\pm$ 0.25
.XX $\pm$ 0.13
.XXX $\pm$ 0.05
ANG $\pm$



ORDER INFORMATION

MJD16-KExx-0606-LF

SERIES | LEADFREE
6P6C
01:G/F
06:6u" GOLD
BLACK
EAR

DESCRIPTION: 6POSITION, 180°, SPLIT PEGS, TOP ENTRY PCB JACK