




STAND OFF(H0.5mm)



DETAIL X

MATERIAL: • HOUSING-PBT POLYESTER UL94V-0
MIXED GLASS FIBER.
STANDARD COLOR-BLACK
• CONTACTS-0.35mm THICK PHOS-BRONZE PLATED
PLATED WITH 6u" HARD GOLD AND GOLD FLASH
IN SOLDER AREA.
• SHIELD-0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.
CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.



PC Board Layout
Ref.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.25
.XX ± 0.13
.XXX ± 0.05
ANG ±



ORDER INFORMATION

MJF13-KX06A36-0808-LF

SERIES
BLACK
06u" GOLD
NON EAR
LEADFREE
8P8C
FRONT TAB 3.68mm

DESCRIPTION: 8POSITION SHIELDED FLAT PIN SIDE ENTRY PCB JACK