

PCB LAYOUT

Ref.

MATERIAL:

- HOUSING—PA9T GN2330  
HEAT RESISTANT PLOYAMIDE RESIN  
BLACK COLOR, UL94V-0
- INSERT HOUSING—PA9T GN2330  
HEAT RESISTANT PLOYAMIDE RESIN  
BLACK COLOR, UL94V-0
- CONTACTS—0.35mm THICK PHOS-BRONZE  
PLATED WITH HARD GOLD AND  
GOLD FLASH IN SOLDER AREA.
- HOLD DOWN—0.30mm THICK COPPER ALLOY,  
PLATED WITH TIN.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS  
PART 68,SUBPART F.

"▽" SHOWS QIP INSPECTION POINT.

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.25  
.XX ± 0.13  
.XXX ± 0.05  
ANG ±

PPOJECTION



**ORDER INFORMATION**

MJW11-KX06-0606-LF

SERIES | | | LEADFREE  
| | | 6P6C  
| | | 06u" GOLD  
| | | NON EAR  
| | | BLACK

DESCRIPTION: 6POSITION SMT TYPE SIDE ENTRY PCB JACK