



Material and Finish

1. Housing: Nylon 6T (UL94V-0), Black.
2. Terminal: Sq. 0.50mm Copper Alloy, Gold Plating.

Electrical Characteristics

1. Current Rating: 1.0 Amp. Max..
2. Dielectric Withstand Voltage: 800V AC RMS for 60Seconds.
3. Insulation Resistance: 1000M Ohms Min. at 500V DC.

Mechanical Characteristics

1. Operating Temperature: -55°C ~ +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

PJECTION

照片框

ORDER INFORMATION

MPVK-VXLW-2X05-LF
SERIES | | | LEADFREE
| | | 10WAY
| | | LOW WINDOW
| | | NON POST
| | | 180°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.00mm Box Header, Molex Type PCB Surface Mount Type Dual Rows 10P, Without Post