



Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 KΩ)
3. At DC = 300V , Insulation Resistance : 20 MΩ Min.
4. Test Condition : Temperature : 25 ± 5°C , Humidity : 50% RH Max.

P1	5	RED	5	P2
	4 (NC)	---	4 (NC)	
	3 (NC)	---	3 (NC)	
	2 (NC)	---	2 (NC)	
	1	BLACK	1	

3	SOCKET CONTACT	4 PCS
2	HOUSING, 5-POS., 2.50mm PITCH, WHITE	2 PCS
1	FLAT RIBBON WIRE, 22 AWG x 2C, UL 1007 (併線)	A/R
ITEM	DESCRIPTION	Q'TY

WIRING TABLE

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

照片框

**ORDER INFORMATION**

**MWX2-050222C1-F20C-LF**

SERIES

5P2C

22 AWG

COMBO WIRE

200mm

LEADFREE

FEMALE TO FEMALE

5P2C

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)

SIZE A4

PPOJECTION

DESCRIPTION: