



Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 KΩ)
3. At DC = 300V , Insulation Resistance : 20 MΩ Min.
4. Test Condition : Temperature : 25 ± 5°C , Humidity : 50% RH Max.

P1	5	YELLOW	5	P2
	4	ORANGE	4	
	3	RED	3	
	2	BROWN	2	
	1	BLACK	1	

WIRING TABLE

3	SOCKET CONTACT	10 PCS
2	HOUSING, 5-POS., 2.50mm PITCH, WHITE	2 PCS
1	FLAT RIBBON WIRE, 24 AWG x 5C, UL 1007 (併線)	A/R
ITEM	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

MWX2-050524C1-F18C-LF

SERIES

LEADFREE
180mm
FEMALE TO FEMALE
COMBO WIRE
24 AWG
05 TO 05 WAY

DESCRIPTION: WIRE HARNESS ASSEMBLY