



Impedance: 50ohm
 Frequency range: 0-3 GHz
 VSWR: 1.05 (max) up to 3 GHz
 Return loss: -32 dB (min)
 Resistor: 50ohm, 1w

4	Contact Pin	BRASS	Silver	1
3	Insulation	PTFE		1
2	Nut	BRASS	Nickel	1
1	Body	BRASS	Nickel	1
NO.	DESCRIPTION	MATERIAL	FINISH	QTY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

0.5-6 = ± 0.1
 6-30 = ± 0.2
 30-120 = ± 0.3
 120-315 = ± 0.5
 315-1000 = ± 0.8
 1000-2000 = ± 1.2
 ANGLES = ± 3'



ORDER INFORMATION

N-MTPQ-50-LF
 SERIES | LEADFREE
 | 50 OHM
 | SQUARE
 | PANEL
 | TERMINATOR
 | PLUG

DESCRIPTION: 50Ω N TYPE MALE FLANGE MOUNT TERMINATOR 1W

www.morethanall.com