



8	GASKET	RUBBER	NONE	1
7	RETAINING	BRASS	NICKEL	1
6	SHELL	BRASS	NICKEL	1
5	FERRULE	BRASS	NICKEL	1
4	GROUND RING	BRASS	NICKEL	1
3	DIELECTRIC	PLASTIC	WHITE	1
2	PIN	BRASS	GOLD	1
1	BODY	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

ELECTRICAL SPECIFICATIONS:

IMPEDANCE: 50 OHM

FREQUENCY RANGE: 0-4 GHz

WORKING VOLTAGE: 1000 VRMS MAX

DIELECTRIC WITHSTANDING: 2500 VRMS MIN

INSULATION RESISTANCE: 5,000 MEGOHMS MIN

CONTACT RESISTANCE:

CENTER CONTACT 3 MILLIOHMS MAXIMUM.

OUTER CONTACT 2 MILLIOHMS MAXIMUM.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

0.5-5	±0.2
5-30	±0.4
30-120	±0.6
120-315	±1
315-1000	±1.6
1000-2000	±2.4

PJECTION

照片框

ORDER INFORMATION

N-PC-400-LF
SERIES | LMR400 | LEADFREE
| CRIMP | MALE

DESCRIPTION: N MALE CRIMP LMR400