



A	Color	B
3	Black	4
5	White	2
7	Green	1
9	Red	3

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL2725 #28*1PR(WHITE, GREEN)+#28*2C(RED, BLACK) +AEB JACKET:BLACK OD:φ3.5 USB2.0	1PCS	E238846
2	HOUSING:	PVK-H-2X05	1PCS	E115256
3	TERMINAL:	PVK-T-22	4PCS	
4	KEY:	2561KEY BLACK	1PCS	
5	HOUSING:	NF-SHBK-2X02	1PCS	
6	TERMINAL:	NF-FT-24	4PCS	
7	SHRINK TUBE:	4φ*15mm BLACK F32	1PCS	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

NFPVK-B02B05BK28-F16N-LF

SERIES

LEADFREE  
406.4mm  
FEMALE TO FEMALE  
28 AWG  
BLACK  
04 TO 10 WAY

DESCRIPTION: CABLE ASS"Y