



SPECIFICATIONS:
 1.VOLTAGE/CURRENT RATING: 30V/0.3A AC;
 2.WITHSTANDING VOLTAGE: 100V AC ONE MINUTE;
 3.INSULATION RESISTANCE: 50MΩ MIN;
 4.CONTACT RESISTANCE: 100mΩ MAX;
 5.OPERATING TEMPERATURE RANGE: -35° C TO 85°

MATERIAL:
 1.INSULATOR: LCP UL 94V-0 BLACK;
 2.TERMINAL: COPPER ALLOY;
 3.METAL FITTINGS: COPPER ALLOY.

PLATING:
 1.TERMINAL: GOLD PLATING,
 NICKEL 50u" MIN. OVER ALL;

No. of contacts	Dimensions	
	A	B
24	6.40	3.70
30	7.60	4.90

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

NP03514-S07X-xxx-LF

SERIES

LEADFREE

024.030 WAY

NON POST

UNMATED HIGH 0.7mm

FEMALE

DESCRIPTION: