



RECOMMENDED P.C.B. LAYOUT

TOLERANCE±0.05

TOP VIEW

**Material:**

**Housing:** High Temperature Plastic UL94V-0.

**Contacts:** Phosphor Bronze.

**Electrical Characteristics:**

**Current Rating:** 0.5 AMP.

**Dielectric Withstanding Voltage:** AC 100V For 1 minute.

**Insulator Resistance:** 50MΩmin. at DC 100V.

**Contact Resistance:** 60mΩmax. at AC 1mA.

**Operating Temperature:** -55°C~+85°C.

100	23.10	20.95	19.60	20.50
90	21.10	18.95	17.60	18.50
80	19.10	16.95	15.60	16.50
72	17.50	15.35	14.00	14.90
70	17.10	14.95	13.60	14.50
60	15.10	12.95	11.60	12.50
50	13.10	10.95	9.60	10.50
40	11.10	8.95	7.60	8.50
34	9.90	7.75	6.40	7.30
30	9.10	6.95	5.60	6.50
26	8.30	6.15	4.80	5.70
24	7.90	5.75	4.40	5.30
22	7.50	5.35	4.00	4.90
20	7.10	4.95	3.60	4.50
16	6.30	4.15	2.80	3.70
14	5.90	3.75	2.40	3.30
12	5.50	3.35	2.00	2.90
10	5.10	2.95	1.60	2.50
Number of Position	A	B	C	D

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±  
X, ±  
.XX ±  
.XXX ±  
ANG ±

照片框

ORDER INFORMATION

NP04-P03P-xxx-LF  
SERIES | | LEADFREE  
| | 010-100WAY  
| | POST  
| | UNMATED HIGH 0.3mm  
| | PLUG

DESCRIPTION: