



RECOMMENDED PCB LAYOUT
CONNECTOR SIDE

PIN NO.	A	B
10	1.60	4.22
16	2.80	5.42
24	4.40	7.02
34	6.40	9.02
40	7.60	10.22

SPECIFICATIONS:

- 1.VOLTAGE/CURRENT RATING: 50V/AC, DC;
- 2.WITHSTANDING VOLTAGE: 150V AC ONE MINUTE;
- 3.INSULATION RESISTANCE: 50M Ω MIN.;
- 4.CONTACT RESISTANCE: 100m Ω MAX.;
- 5.OPERATING TEMPERATURE RANGE: -35° C TO 105° C.

MATERIAL:

- 1.INSULATOR: LCP UL 94V-0 BLACK;
- 2.TERMINAL: COPPER ALLOY;

PLATING:

- 1.TERMINAL: GOLD PLATING NICKEL 50u" MIN. OVER ALL;

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ± 0.30
.XX ± 0.25
.XXX ± 0.15
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

NP04146-S09X-xxx-LF

SERIES

LEADFREE

010-060WAY

NON POST

UNMATED HIGH 0.9mm

FEMALE

DESCRIPTION: