



RECOMMENDED PCB LAYOUT

SPECIFICATIONS:

- 1.VOLTAGE/CURRENT RATING: 30V/0.3A AC;
- 2.WITHSTANDING VOLTAGE: 100V AC ONE MINUTE;
- 3.INSULATION RESISTANCE: 50MΩ MIN;
- 4.CONTACT RESISTANCE: 100mΩ MAX;
- 5.OPERATING TEMPERATURE RANGE: -35° C TO 85° C.

MATERIAL:

- 1.INSULATOR: LCP UL 94V-0 BLACK;
- 2.TERMINAL: COPPER ALLOY;
- 3.METAL FITTINGS: COPPER ALLOY.

PLATING:

- 1.TERMINAL: GOLD PLATING,
NICKEL 50u" MIN. OVER ALL;

PIN NO.	DIM A	DIM B
10	4.40	1.60
24	7.20	4.40
30	8.40	5.60
40	10.40	7.60
50	12.40	9.60
60	14.40	11.60

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

NP0415-S07X-xxx-LF

SERIES

LEADFREE
010-060WAY
NON POST
UNMATED HIGH 0.7mm
FEMALE

DESCRIPTION: BTB PH0.4MM H:0.8MM SOCKET

煜倫股份有限公司

www.morethanall.com