



NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0. COLOR: BLACK.
 - 1.2 CONTACT: COPPER ALLOY.
2. FINISH:
 - 2.1 CONTACT:
 - 50~100u" NICKEL UNDERPLATING OVERALL.
 - 1: GOLD FLASH PLATING ON CONTACT AREA.
 - C: 15u" GOLD PLATING ON CONTACT AREA.
 - 2.2 SOLDER:
 - 50~100u" NICKEL UNDERPLATING OVERALL.
 - 1: GOLD FLASH PLATING ON SOLDER TAILS.
 - C: GOLD FLASH PLATING ON SOLDER TAILS.
3. REFLOW SOLDER CAPABLE TO 260°C

RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

| CKTS | DIM A | DIM B |
|------|-------|-------|
| 70 | 13.60 | 15.52 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X ± 0.50

CHECKED BY GENIUS

.X ± 0.25

UNIT / mm

SCALE 1 : 1

.XX ± 0.15

DATE

.XXX ± 0.10

ANG ± 2°

照片框

ORDER INFORMATION

NP04185-P01XC-070-LF

SERIES | | | | LEADFREE
| | | | 070 WAY
| | | | MYLAR
| | | | NON POST
| | | | UNMATED HIGH 1.45mm
MALE

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION: