

NOTE:

1. MATERIAL

HOUSING MATERIAL: LCP, COLOR: BLACK;

CONTACT MATERIAL: COPPER ALLOY, GOLD PLATED AT CONTACT AREA;


2. PERFORMANCE:

CONTACT RESISTANCE: 80mOHM Max.


DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR 1MINUTE;

INSULATION RESISTANCE: 100MOHM Min.

DURABILITY: 30 CYCLES Min.



60	NP0419-P01X-060	11.60	13.10
50	NP0419-P01X-050	9.60	11.10
40	NP0419-P01X-040	7.60	9.10
34	NP0419-P01X-034	6.40	7.90
30	NP0419-P01X-030	5.60	7.10
24	NP0419-P01X-024	4.40	5.90
20	NP0419-P01X-020	3.60	5.10
CIRCUIT SIZE	PART NUMBER	DIM A	DIM B



MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

TOLERANCES ARE

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

NP0419-P01X-xxx-LF

SERIES

LEADFREE
020~060WAY
NON POST
UNMATED HIGH 0.1mm
PLUG

DESCRIPTION: BOARD TO BOARD CONN 0.40MM PITCH, MALE 1.50 MATING HEIGHT