

RECOMMENDED PC BOARD
PATTERN DIM.(REF.)

NOTES:

1. MATERIAL:


- 1.1 HOUSING: THERMOPLASTIC HIGH TEMP,
UL94V-0; COLOR:NATURAL.
- 1.2 CONTACT: COPPER ALLOY

2. FINISH:

- 2.1 CONTACT:

UNDER PLATING: 50u" MIN. NICKEL OVERALL.
FINISH:SEE ORDER INFORMATION.

| CKTS | Dim A | Dim B |
|------|-------|-------|
| 20 | 3.60 | 6.00 |
| 22 | 4.00 | 6.40 |
| 24 | 4.40 | 6.80 |
| 26 | 4.80 | 7.20 |
| 30 | 5.60 | 8.00 |
| 40 | 7.60 | 10.00 |
| 50 | 9.60 | 12.00 |
| 60 | 11.60 | 14.00 |
| 70 | 13.60 | 16.00 |
| 80 | 15.60 | 18.00 |
| 100 | 19.60 | 22.00 |



MATED CONDITION (REF.)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

照片框

ORDER INFORMATION

NP0421-P01X-xxx-LF

SERIES

LEADFREE
020~100WAY
NON POST
UNMATED HIGH 0.1mm
MALE

DESCRIPTION: 0.4 PITCH BTB PLUG CONN. SMT S/T TYPE ASS'Y H=1.5