



- NOTES:
- MATERIAL:
 - HOUSING: THERMOPLASTIC LCP, HIGH TEMP., UL94V-0; COLOR:BLACK.
 - CONTACT: PHOSPHOR BRONZE
 - FITTING NAIL: COPPER ALLOY
 - FINISH:
 - CONTACT: GOLD FLASH PLATING
50~100u" NICKEL UNDERPLATING OVERALL.
 - FITTING NAIL: 80~120u" MATT TIN PLATING ON SOLDER TAILS.
50~100u" NICKEL UNDERPLATING OVERALL.
 - REFLOW SOLDER CAPABLE TO 260°C

CKT	Dim A	Dim B	Dim C	Dim D	MYLAR SIZE
10	5.10	3.50	2.44	1.60	
12	5.50	3.90	2.84	2.00	2.5
20	7.10	5.50	4.44	3.60	
24	7.90	6.30	5.24	4.40	
26	8.30	6.70	5.64	4.80	3.0
30	9.10	7.50	6.44	5.60	
34	9.90	8.30	7.24	6.40	
40	11.10	9.50	8.44	7.60	
50	13.10	11.50	10.44	9.60	5.0
60	15.10	13.50	12.44	11.60	
70	17.10	15.50	14.44	13.60	10.0
80	19.10	17.50	16.44	15.60	15.0

RoHS Compliant

TOLERANCES ARE

DRAWING BY CY X ± 0.50
 CHECKED BY GENIUS X ± 0.25
 UNIT / mm SCALE 1 : 1 .XX ± 0.15
 .XXX ± 0.10
 ANG ± 2°

DATE
 SIZE A4 PPROJECTION

ORDER INFORMATION

NP0421-S14PCR-xxx-HF
 SERIES REEL MYLAR POST
 FEMALE UNMATED HIGH 1.4mm
 HALOGEN FREE
 010~080WAY

DESCRIPTION: 0.4mm BTB D/R RCPT SMT S/T TYPE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 焯倫股份有限公司
 www.morethanall.com

