


NOTE




1. No rust, contamination, damage nor deformation effecting on function.
2. TITLE → ** number of pins

TABLE

NO	DESCRIPTION	MATERIAL	FINISH
A	BASE	LCP	BLACK COLOR
B	TERMINAL	Phosphor Bronze	Au , underplating Nickel

DIMENSION TABLE

PINS	POSITION	A	B	C
16		2.80	3.80	4.70
18		3.20	4.20	5.10
20		3.60	4.60	5.50
24		4.40	5.40	6.30
26		4.80	5.80	6.70
30		5.60	6.60	7.50
34		6.40	7.40	8.30
40		7.60	8.60	9.50
50		9.60	10.60	11.50
54		10.40	11.40	12.30
60		11.60	12.60	13.50



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

NP0431-P01XR-xxx-LF

SERIES

LEADFREE

016~060WAY

MALE

REEL

NON POST


UNMATED HIGH 0.1mm

煜倫股份有限公司


www.morethanall.com

DESCRIPTION: H=0.9mm 0.4PITCH B TO B MALE ASSEMBLY

【 REFERENCE 1 】



【 REFERENCE 2 】



◆ EMOSS TAPE SPECIFICATION

【 REFERENCE 1 】

- 1) QUANTITY : 3,000pcs / 1 Reel
- 2) Beginning portion - Empty 20mm min , Ending portion - Empty 40mm min. (REEL 20mm , 40mm)
- 3) Peel strength of cover tape : 10~70gf
- 4) Peeling speed : 300mm/minute
- 5) Peeling angle : 165° ~ 180°
- 6) Cover Tape : 0.06 ~ 0.07mm

【 REFERENCE 2 】

- 1) Product angle in pocket would be tilt : 3.0°


<< NOTE >>

1. Reel 3,000ea packing (1REEL 3,000ea)
2. BOX Packing
 - ▷ 16p~20p → BOX 13reel packing : Quantity = 39,000ea
 - ▷ 24p~60p → BOX 10reel packing : Quantity = 30,000ea
3. Horizontal packing (REEL)
4. Outer carton box size : 350(width) × 350(length) × 350(high)
5. Adhesive of Label.


【TABLE】

NO.	NAME	MATERIAL
A	OUTER CARTON BOX	Corrugated cardboard
B	REEL	HIPS

【INNER PACKING】



【OUTER PACKING】



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

NP0431-P01XR-xxx-LF

SERIES

LEADFREE

016~060WAY

MALE

REEL

NON POST

UNMATED HIGH 0.1mm

DESCRIPTION: