



A = 0.50 * No. of Spaces

B = A + 3.5

D = A + 1.5

4*(Available : 10,16,20,22)

Circuits not found above please consult manufacturer


Material:

* Insulator:

High temperature Polyamide UL 94V-0

Color Nature(Beige)

* Contact: Copper alloy



Recommended P.C. Board Layout

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±
.X ± 0.25
.XX ± 0.13
.XXX ± 0.08
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

NP0519-S10XR-xxx-LF

SERIES

LEADFREE

010~022 WAY


REEL

NON POST

UNMATED HIGH 1.0mm


FEMALE

DESCRIPTION: 0.50mm(.002") Board To Board Receptacle Connector (For Mating height 1.5mm)



1. 10 sprocket hole pitch cumulative tolerance ± 0.20 .
2. Carrier camber is within 1 mm in 250 mm.
3. Material : Clear,Transparent Polystyrene Alloy (UP-6000).
4. All dimensions meet EIA-481-B requirements.
5. Thickness : 0.30 ± 0.05 mm.
6. Packing length per 22" reel : 75 Meters.
7. Component load per 13" reel : 2000 pcs.

Circuits	Dimension					Packing (Reel/Caton)
	E	F	W1	W2	W3	
10,16,20	16.0(.630)	—	16.5(.650)	22.5(.886)	16.5(.650)	11
22	24.0(.945)	—	24.5(.965)	30.5(1.200)	24.5(.965)	9



WIDTH : 16,24 mm Carrier